



AUTOMATIC XY CUTTER OF FLEXIBLE MATERIALS

High performing cutting machine with rotating blades for X and Y trimming
of flexible materials from roll to sheets.

- > Combined horizontal and vertical cutting for the fastest finish for your printed and unprinted rolls
- > High performing trimmer: cut one roll of 50 meters (164 ft.) in 3 minutes
- > Precise cutting: trimmed images perfectly square every time
- > 3 operation modes: crop mark (useful to trim multiple printing sizes from the same roll), automatic and manual


Even more intuitive set up parameters thanks to the new designed user-friendly software (LCD touch screen display). New **MUTING** function that avoids possible misreading of hidden marks

- > Long term reliability and safety combined with low maintenance costs

SUITABLE FOR:

- Paper (also laminated or encapsulated)
- Wallpaper
- Vinyl & self adhesive vinyl
- Backlit & frontlit display
- Reflective material
- PVC banner (up to 900 gr/m² - 27 oz./ya²)
- Magnetic rubber
- Polycarbonate (film)
- Canvas & polyester (with liner)
- Many more..





Fine positioning of the cutting blades (optional)



Advanced cutting mark reader



New software design for better usability




Unwinding shaft brake for adjusting the tension of the material



Fine pressure adjustment (according to the types of material)



Aluminium 3" shaft with flanges for the right alignment of the roll



Adjustable unwinding shaft (optional)



Single lengthwise rotary crush cutter (twin cutters optional)



Adjustable collecting table (optional)

	MIURA II 160	MIURA II 265
Working width	1650 mm (65 in)	2650 mm (105 in)
Maximum cutting thickness	1,2 mm (0,04 in)	1,2 mm (0,04 in)
Feeding speed	1 - 30 m/min. (3 - 98 ft/min)	1 - 30 m/min. (3 - 98 ft/min)
Usable cutting units	max. 8	max. 8
Cross cutting speed	5 - 120 m/min. (16 -393 ft./min)	5 - 120 m/min. (16 -393 ft./min)
Max. roll diameter	300 mm (12 in)	300 mm (12 in)
Max. roll weight	60 kg (132 lb)	60 kg (132 lb)
Power supply	230 V - 50 Hz - 650 W	230 V - 50 Hz - 650 W
Dimensions (W x D x H)	2400 x 1000 x 1350 mm (99 x 40 x 51 in)	3500 x 1000 x 1350 mm (137 x 40 x 51 in)
Weight	280 kg (617 lb)	460 kg (1014 lb)
Packing Dimensions (W x D x H)	2650 x 1300 x 1400 mm (104 x 51 x 55 in)	3710 x 1150 x 1600 (146 x 45 x 63 in)
Packing Weight	375 kg (827 lb)	545 kg (1201 lb)

Distributor

Manufactured in compliance with CE regulations



100% Made by FLEXA



100% Made in Italy

Follow us:

